


NOCTIS LUX 3 50W floodlight with motion sensor




CE

Power	50 W	Voltage	230 V
Luminous flux*	4500 lm (120°)	Colour of light	NW
Beam angle	100 °	IK	07
Degree of protection (IP)	IP44		




See more on dedicated page 




 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI029055NW_CZUJNIK_PW
Power	50 W
Nominal current	220 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4500 lm (120°)
Luminous flux**	4500 lm (360°)
Lamp efficacy	90 lm/W
Colour of light	NW
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	180x215x53 mm
Weight	0.579 kg
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux