

## SLI028026NW PW




CE

---


Power	<b>52 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>8900 lm (360°)</b>	Colour of light	<b>NW</b>
Beam angle	<b>120 °</b>	IK	<b>10</b>
Degree of protection (IP)	<b>IP65</b>		

---



 User manual



 Declaration of Conformity



 Photometric file

**Technical data:**

Code	SLI028026NW_PW
Power	52 W
Nominal current	235 mA
Voltage	230 V
Energy efficiency class	C
Energy consumption	52 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.99
Useful luminous flux*	8900 lm (360°)
Luminous flux**	8000 lm (360°)
Lamp efficacy	171 lm/W
Luminous intensity	2500 cd
Colour of light	NW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	3
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	POLYCARBONATE
IK	10
Degree of protection (IP)	IP65
Colour	Gray/White
Dimension (AxBxC)	1490x72x70 mm
Weight	1.5 kg
For use	Inside/Outside
Assembly method	On the ceiling/Suspended
Application	INT/EXT
Number of pieces on the packaging	12 pcs.
Made in	PRC
Other	max 16szt w lini



\*applies to the LED source used. \*\*Luminaire luminous flux