

MAH LED N

Prachotesné LED svietidlo



[V] 220-240 AC	[Hz] 50	≥ 15000	[h] 30000	ellipse $\leq 6x$ MacAdam	Ra 80	SMD
		IP 65		[°C] -20 ÷ 40		IK 08
	[mm ²] 1,5 ÷ 2,5	m 0,5m				



MAH-LED N 20W-NW/PC

	[W]	[lm]	Tc [K]	[°]	
MAH-LED N 20W-NW/PC	22603	20	2100	4000	X135/Y100 sivá
MAH-LED N 40W-NW/PC	22604	40	4200	4000	X135/Y100 sivá
MAH-LED N 50W-NW/PC	22605	50	5250	4000	X135/Y100 sivá

Kanlux MAH LED N sú hermetické svietidlá určené pre náročnejších užívateľov. Vyznačujú sa výnimočnou svetelnou účinnosťou až 105 lm/W a schopnosťou pripojiť až 15 svietidiel (v závislosti na modele), čo umožňuje osvetlenie veľkých plôch.

- Materiál korpusu: PC
- Materiál difúzora: PC

MAH LED N

Prachotesné LED svietidlo



MAH-LED N 20W-NW/PC




MAH-LED N 40W-NW/PC




MAH-LED N 50W-NW/PC



MAH-LED N 20W



MAH-LED N 40W



MAH-LED N 50W