

SLI029058NW PW




---


Power	<b>150 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>13600 lm (120°)</b>	Colour of light	<b>NW</b>
Beam angle	<b>85 °</b>	IK	<b>08</b>
Degree of protection (IP)	<b>IP65</b>		

---




 User manual



 Declaration of Conformity

Technical data:

Code	SLI029058NW_PW
Power	150 W
Nominal current	655 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	150 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.99
Useful luminous flux*	13600 lm (120°)
Luminous flux**	13600 lm (360°)
Lamp efficacy	91 lm/W
Luminous intensity	7800 cd
Colour of light	NW
Beam angle	85 °
RA	>80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	Aluminum+PC LENS
IK	08
Degree of protection (IP)	IP65
Colour	Gray
Dimension (AxBxC)	360x262x30 mm
Weight	1.525 kg
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



\*applies to the LED source used. \*\*Luminaire luminous flux