


ALGINE PREMIUM led panel




Power	30 W	Voltage	230 V
Luminous flux*	4400 lm (360°)	Colour of light	NW
Beam angle	120 °	IK	06
Degree of protection (IP)	IP20		



See more on dedicated page 



 User manual



 Declaration of Conformity

Technical data:

Code	SLI035049NW
Power	30 W
Nominal current	135 mA
Voltage	230 V
Energy efficiency class	D
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Luminous flux*	4400 lm (360°)
Luminous flux**	3800 lm (360°)
Lamp efficacy	146 lm/W
Colour of light	NW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	3
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x12 mm
Mounting hole	575x575 mm
Weight	2.82 kg
For use	Inside
Assembly	In the ceiling/On the ceiling/Pendant
Application	INT
Number of pieces on the packaging	5 pcs.
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux